

 <p>PG PARS CO. Corrosion control &amp; Cathodic protection شانت پارس انجمن مهندسان خوردگی و حفاظت کاتدی</p> <p>Info@pgpars.com www.pgpars.com</p>	<p><b>PG PARS CO.</b></p> <p><b>Design , Consultation , Production &amp; Implementation of Cathodic Protection Systems</b></p>	<p><b>Client's Logo</b></p>
<p><b>Project:</b></p>		
<p><b>Document Title:</b></p>	SHANT Data Sheet	
<p><b>Document Number:</b></p>		<p>Rev:01 <span style="margin-left: 100px;">Page 1 of 2</span></p>

# Shant Current Data Sheet

		<b>STATUS</b>
DATE:		APPROVED
		APPROVED WITH COMMENTS
SIGNATURE:		COMMENTED
		REJECTED
Next Issue Description		

REV.	DATE	DESCRIPTION	PREPARED	CHECKED	APPROVED
		PG PARS CO.			

 <p>PG PARS CO. Corrosion control &amp; Cathodic protection شرکت پی پارس انجمن تخصصی حفاظت کاتدی</p> <p>Info@pgpars.com www.pgpars.com</p>	<p><b>PG PARS CO.</b></p> <p><b>Design , Consultation , Production &amp; Implementation of Cathodic Protection Systems</b></p>	<p><b>Client's Logo</b></p>
<p><b>Project:</b></p>		
<p><b>Document Title:</b></p>	SHANT Data Sheet	
<p><b>Document Number:</b></p>		<p>Rev:01 <span style="float: right;">Page 2 of 2</span></p>

1.	SHANT	
1.1	Reference	IEC 60904-2
1.2	Chemical Component	Copper 55-60%, 2-3.8% Lead, Resin Remainder
1.3	Dimention	40 * 10 * 150 mm
1.5	Weight	300g
1.6	Branch Size	100 mm
1.7	Refrence voltage	75mv
1.8	Max Current	50 Amp
1.9	Origin	IRAN